

# 大型电机定子扇形片 长形槽

序号	产品型号	图号	工装号	A1外弦	A2内弦	Φ1外径	Φ2内径	β	B槽宽	B槽长	g槽楔	槽楔总长	r1槽底	r2槽楔	α1内角	α2外角片	槽数Φ	D拉紧螺孔	备注
1	TR800-6/1400		10003-001	478.8	348.84	1400	1020	40°	17.5	15	5	98	1	1	60°	30°			
2	YK12-40	SEY. 670. 057	10003-002	447.76	346.82	1200	1240	20°	17.2	0.5	4.5	105	1	1	60°	30°			
3	YK2200-2	SEY. 660. 971	10003-003	590	284	1180	988	60°	19	1	5	113	1	1	60°	30°			燕尾螺孔
4	YD17/83-4		10003-005	581	389.9	1700	1140	40°	22	0.5	6	85.5	1	1	60°	30°			燕尾螺孔
5	SEY. 670. 050	SEY. 670. 050	10003-006	580	370	1160	740	60°	17	0.5	5	94.5	1	1	60°	30°			燕尾螺孔
6	YGL118/101-320/2	SEY. 670. 218	10003-008	590	284	1180	988	60°	19	1	5	130	1	1	60°	30°			燕尾螺孔
7	YK13/44-12		10003-009	489.03	376.2	1430	1100	40°	17.2	0.5	4.5	78	1	1	60°	30°			
8	TMK313/29-24	SEY. 670. 063	10003-010	728.5	619.1	2130	1810	40°	12.7	0.5	4	69	1	1	60°	30°			9-162
9	TDK118/26-14	SEY. 670. 082	10003-011	403.584	307.81	1180	900	40°	12.6	0.5	3.5	76	1	1	60°	30°			9-90
10	TMK1000-36	SEY. 670. 045/093/632	10003-012	451.49	402.9	2600	2320	20°	13	0.5	3.5	65	1	1	60°	30°			18-216
11	TMK1250-40	SEY. 670. 218	10003-014	594.36	503.5	3250	2900	20°	13	0.5	4.5	105	1	1	60°	30°			双圆螺孔孔
12	IKZ-143-2	SEY. 660. 1066	10003-015	715	350	1430	700	60°	22	20	5	133	1	1	60°	30°			Y400-2/130
13	YK4000-24	SEY. 670. 0004	10003-018	750.52	657.4	2900	2540	30°	15.4	0.5	4.5	95	1	1	60°	30°			SEY. 670. 226代替此号
14	Y1000-16/1730		10003-019	591.66	478.8	1730	1400	40°	17.2	0.5	4.5	75	1	1	60°	30°			9-108
15	TK180-18/1430	SEY. 670. 076	10003-021	489.06	396.7	1430	1160	40°	14.4	0.5	3.5	80	1	1	60°	30°			9-108
16	TMK900-60	SEY. 670. 078	10003-022	370.4	346	4250	3970	10°	16	0.5	4.5	85	1	1	60°	30°			36-288
17	TMK900-60	SEY. 670. 079	10003-023	370.4	346	4250	3970	20°	16	0.5	4.5	85	1	1	60°	30°			18-288
18	TF4000-14	SEY. 670. 085	10003-026	672.93	559	2600	2160	30°	21	0.5	5.5	115	1	1	60°	30°			12-168
19	Y800-2-10	SEY. 670. 084/668	10003-027	427.53	338.5	1250	990	40°	17.8	0.5	4.5	68.5	1	1	60°	30°			9-90
20	15-φ. 8		10003-028	378.8	267.8	990	700	45°	15.2	1.25	4	70.25	1	1	60°	30°			8-72
21	Y900-4	SEY. 670. 1059	10003-029	700	455	1400	910	60°	18	1	5	106	1	1	60°	30°			6-72
22	TR800-6/1180	SEY. 670. 087	10003-030	590	284	1180	988	60°	19	1	5	113	1	1	60°	30°			2006 新版
23	YD1500/850-10/12	SEY. 670. 089	10003-033	728.5	581.43	2130	1700	40°	12.4	0.5	4.5	110	1	1	60°	30°			9-144
24	Y4800-1-16	SEY. 670. 096	10003-034	625	495	1250	990	60°	17.8	0.5	4.5	76	1	1	60°	30°			6-96
25	QFK-3-2	SEY. 670. 303	10003-035	525		1050	560	60°	15.8	3	6	70	1	1	60°	30°			6-60
26	发电机		10003-037																
27	Y250-14/1250	SEY. 670. 124	10003-038	427.5	338.6	1250	990	40°	12	0.5	4.5	70	1	1	60°	30°			9-126
28	T40W-6/30	SEY. 670. 095/657	10003-039	735.34	628.6	2150	1838	40°	20.2	0.5	5.5	86	1	1	60°	30°			9-144
29	发电机		10003-040																
30	YK1250-2/1250	SEY. 670. 1138	10003-041	625	330	1250	660	60°	22	1	5	98	1	1	60°	30°			6-48
31	YK90-2	SEY. 670. 141	10003-047	625	425	1250	938	60°	18.3	0.5	4.5	124	1	1	60°	30°			9-96
32	TK630-20/1730	SEY. 670. 137/635	10003-043	591.69	495.9	1730	1450	40°	14.4	0.5	4.5	76	1	1	60°	30°			9-126
33	TMK600-24	SEY. 670. 138	10003-044	735.34	632.74	2150	1850	40°	12.6	0.5	3.5	78	1	1	60°	30°			9-126
34	Y1250-4/1160	SEY. 660. 1144	10003-046	580	370	1160	740	60°	17	0.5	5	94.5	1	1	60°	30°			燕尾螺孔
35	YD1500/1750-8/10	SEY. 670. 141	10003-047	591.66	451.5	1730	1320	40°	13.6	0.5	4.5	114	1	1	60°	30°			6-72
36	发电机	SEY. 670. 144	10003-048	550	292.57	1100	660	60°	16	3	6	85	1	1	60°	30°			双燕尾螺孔(上:36/下:55高20)
37	TI250-8/1430	SEY. 670. 150	10003-049	489.09	367.33	1430	1074	40°	19.8	0.5	4.5	88	1	1	60°	30°			9-90
38	TK250-16/1430	SEY. 670. 151	10003-050	441.89	358.46	1430	1160	36°	11.8	0.5	3.5	74	1	1	60°	30°			10-120
39	TF3200-28/2320	SEY. 670. 159	10003-052	564.36	503.58	3250	2900	20°	17.2	0.5	4.5	100	1	1	60°	30°			18-252
40	发电机	SEY. 670. 167	10003-053	612.29	301.725	1600	770	45°	19	7.5	12.5	127	1	1	60°	30°			9-48
41	TK1800-16/2150	SEY. 670. 179/661	10003-057	735.34	622.48	2150	1820	40°	17.2	0.5	4.5	78	1	1	60°	30°			双燕尾螺孔(上:36/下:55高20)
42	YK300-20/1600	SEY. 670. 189	10003-058	547.23	458.31	1600	1340	40°	13	0.5	4.5	75	1	1	60°	30°			9-144
43	TK3200-18/2600	SEY. 670. 192	10003-059	540.57	465.72	2600	2240	24°	17.2	0.5	4.5	90	1	1	60°	30°			15-180
44	TK300-1250-6/1180	SEY. 670. 196	10003-060	590	410	1180	820	60°	15.5	0.5	4.5	70	1	1	60°	30°			6-72
45	TK320-12/1430	SEY. 670. 199	10003-061	489.09	383.158	1430	1150	40°	18.5	0.5	4.5	80	1	1	60°	30°			9-108
46	TK400-22/2320	SEY. 670. 201/636	10003-062	489.1	324.9	1430	950	40°	20	0.5	5.5	74	1	1	60°	30°			9-72
47	TMK800-36	SEY. 670. 212	10003-065	451.49	402.56	2600	2320	20°	16.8	0.5	4.5	76	1	1	60°	30°			18-162
48	TK250-14/1180	SEY. 670. 220	10003-067	403.58	307.82	1180	900	40°	15.8	0.5	4.5	82	1	1	60°	30°			9-90
49	YF900-6-12	SEY. 670. 233	10003-070	427.53	338.6	1250	990	40°	17.6	0.5	4.5	85	1	1	60°	30°			9-90
50	T40W-6/30-260	SEY. 670. 231	10003-071	590	292.57	1100	660	60°	18.5	0.5	4.5	105	1	1	60°	30°			16-192
51	TK4000-22/2320	SEY. 670. 232	10003-072	564.36	493.16	3250	2840	20°	20.5	0.5	5.5	110	1	1	60°	30°			18-216
52	T3200-6/1730	SEY. 670. 235/652	10003-073	534.6	383.18	1730	1240	36°	21	0.5	5.5	95	1	1	60°	30°			10-90
53	YF900-6-12	SEY. 670. 237	10003-074	444.6	338.6	1300	990	40°	17.6	0.5	4.5	85	1	1	60°	30°			9-90
54	YK2000/1800-8/10/1730	SEY. 670. 239	10003-075	452.93	336.46	1730	1300	30°	18.2	0.5	4.5	107	1	1	60°	30°			12-120
55	YK800-4	SEY. 660. 1578	10003-076	625	405	1250	810	60°	19.5	1	5	108	1	1	60°	30°			6-72
56	TK4000-18/2600	SEY. 670. 241 / 655	10003-077	540.27	463.64	2600	2230	24°	18.5	0.5	4.5	98	1	1	60°	30°			15-180
57	YK5710-2	SEY. 660. 1665	10003-078	590	310	1180	620	60°	22	1	5	112	1	1	60°	30°			6-48
58	TMK400-32	SEY. 670. 242	10003-079	735.34	646.42	2150	1890	40°	14	0.5	4	62	1	1	60°	30°			9-162
59	YK5710-8	SEY. 670. 247	10003-081	590	425	1180	850	60°	17.2	0.5	4.5	83	1	1	60°	30°			6-72
60	YK110-4	SEY. 670. 249	10003-083	590	385	1180	790	60°	18.5	0.5	4.5	78	1	1	60°	30°			6-60
61	YK110-4	SEY. 670. 250	10003-083	590	385	1180	790	60°	17.5	0.5	4.5	74	1	1	60°	30°			6-72
62	YD1800/1250-	SEY. 670. 254	10003-084	547.23	427.53	1600	1250	40°	18.5	0.5	4.5	111	1	1	60°	30°			9-108
63	Y1050-4	SEY. 670. 256	10003-085	715	454.5	1430	909	60°	22	15	5	127	1	1	60°	30°			燕尾螺孔
64	YK800-4	SEY. 670. 260	10003-087	725	485	1450	970	60°	24.6	8	5	116	1	1	60°	30°			6-72
65	T2200-6/1730	SEY. 670. 266	10003-088	534.6	383.18	1730	1240	36°	17.2	0.5	5.5	87	1	1	60°	30°			10-90
66	QFKW-15-2	SEY. 670. 269	10003-089	694.21	334.09	1600	710	51° 26'	22.4	2	12	152	1	1	60°	30°			7-42
67	YKX1000-8	SEY. 670. 272	10003-090	447.76	346.82	1730	1340	30°	17.8	0.5	4.5	95	1	1	60°	30°			12-120
68	YR2800-14/2150	SEY. 670. 270	10003-091	735.34	601.96	2150	1760	40°	16.2	0.5	4	92	1	1	60°	30°			9-126
69	TMK2200-32/2600C	SEY. 6																	

118	TAW3600-20	8EY. 670. 623	1G003-149	切角530 未切角 540.57	467.8	2600	2250	24°	15	0.5	4.5	86	1	1	60°	30°	15-180	2-φ25.3		价格41500
119	YR1600-8	8EY. 670. 626	1G003-150	切角690 未切角715	560	1430	1120	60°	17.4	1	4	69	0.5	0.5	60/10°		6-96	2-φ25.3		价格67000
120	YRKK1120-12	8EY. 670. 628	1G003-151	切角630 未切角 632.74	513.03	1850	1500	40°	14.2	1	4	97	0.5	0.5	60/10°		9-144			
121	QFW-11-2	8EY. 670. 637	1G003-152	切角725 未切角 774.57		1550	776	60°	19.2	7.5	12.5	141	1				6-60		双跨尾槽（相对，不顺眼）	
122	YRKK1250-14	8EY. 670. 659	1G003-153	切角725 未切角 735.34	622.48	2150	1820	40°	18.7/19	1	4	85	0.5	0.5	60/10°		9-126	2-φ32.3		价格65000
123	T6700-6/1730	8EY. 670. 664	1G003-154	切角560 未切角 591.69	437.79	1730	1280	40°	17.2	0.5	4.5	75	1	1	60/30°		9-108	2-φ31.3H11		
124	YK3200-2/1340	8EY. 670. 670	1G003-156	458	250	1340	730	40°	19.5	15	4.5	106	1	1	60/30°		9-54	2-φ24.5		
125	TMB2500-40/3250	8EY. 670. 671	1G003-157	564.36	517.47	3250	2980	20°	16	0.5	4	64	1	1	60/30°		18-216	2-φ25.3		
西法	YAPT8800-8	8SD. 671. 003	1G003-158	670	456	1340	990	60°	17.2	1	5	85.5	1	1	0	20°	6-84	2-21H11		
西法	YPTM900-8	8SD. 671. 004	1G003-159	715	530	1430	1060	60°	19.2	1	5	88.5	0.6	1	0	20°	6-72	2-21 <sup>0.15</sup>		